## Description

A special product from the LITHOFIN-Range for marble, natural and engineered stone (MN). Lithofin MN Power-Clean is free of solvents, low in odour and economical in use. It is a mildly alkaline cleaner, which contains a balanced mixture of cleaning components which guarantee optimal performance.

## **Properties**

This special cleaner is nearly odourless and highly economic. Lithofin MN Power-Clean removes grease and oil, all kinds of general and ingrained dirt as well as floor polish residues, old acrylic emulsions, care products, etc.

<u>Technical Data:</u> Density: approx. 1,0 g/cm<sup>3</sup> Appearance: liquid, colourless, clear Odour: pleasant pH-Value: approx. 10 Flash Point: n.a. Solubility in Water: complete

## Field of Use

For thoroughly cleaning used or exceptionally dirty natural stone surfaces and for initially cleaning newly laid surfaces. Suitable for use on polished, finely honed and rough marble and other natural stones. Facilitates removing cement residues from polished marble. Suitable for indoor and outdoor use.

## **Directions for Use**

Apply and evenly distribute Lithofin MN Power-Clean diluted up to 1:10 and wipe the surface. In case of stubborn dirt deposits, apply undiluted or diluted up to 1:5 with a brush and distribute. Allow the product to work for 10 to 20 minutes; brush occasionally. Do not allow to dry, add water if necessary. Brush again before wiping up. On large areas, use a squeegee to remove the product. Wash the surface thoroughly with clean water. If the result is not satisfying, repeat the process allowing the product to work longer and brushing more vigorously.

<u>Please Note:</u> avoid splashes on sensitive areas such as metal or wood, painted or varnished surfaces, wall paper, etc. Always test the product in an inconspicuous area prior to use. Coverage:

as supplied: approx. 5 to 10m<sup>2</sup> depending on dirt diluted: up to 30m<sup>2</sup>

<u>Advice:</u> for removing wax layers and the like, we recommend Lithofin WAX-OFF.

For cement residues and rust discolorations on granite, gneiss and similar acid resistant stones, use Lithofin MN Builder's Clean.

# Lithofin MN Power-Clean

### Storage

Keep closed, cool and dry. Not above 25℃. Shelf life of up to three years.

### **Environmental Protection**

Surfactants are biologically degradable in accordance with EU-regulations. Free of phosphates. <u>Disposal:</u> diluted product may be added to waste water. Containers are made of environmentally friendly polyethylene (PE). Clean containers can be recycled through collection systems.

## Safety

<u>Contents:</u> 5-15% non-ionic surfactant; solubilizer; auxiliary agents; scent geraniol.

Labelling according to EG-Guideline 199/45/EG: Xi, irritant.

<u>Risk and Safety Phrases:</u> irritating to eyes. Keep out of the reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately and show container or label.

Advice: As with all cleaners avoid prolonged contact with skin or wear rubber gloves, if you have sensitive skin.

<u>First Aid Procedures:</u> in case of inhalation take in fresh air. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. Do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

<u>Emergency Procedures:</u> in case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). Ensure adequate ventilation. Product does not burn, fire-extinguishing activities according to surrounding.

<u>Additional Information</u> is listed on the Material Safety Data Sheet.

ADR2003:

not a dangerous good.

#### Packaging

500ml bottle with child-proof cap (10 per box) 1 litre bottle with child-proof cap (10 per box) 5 litre canister (2 per box)

Please Note: statements concerning environmental and safety issues refer to the product as delivered (concentrated). This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (GB1.11gps/1.10)